



according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Eosin Y solution Ulm

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Waldeck GmbH & Co KG

Division Chroma Havixbecker Str. 62

Street: Havixbecker Str. 6
Place: D-48161 Münster

Post-office box: 410180

D-48065 Münster

+49(0)180/2247662

Telephone: +49(0)180/2247662 Telefax: +49(0)180/1247662

Responsible Department: Labor

Mo. – Do.: 08.00 – 17.00 Uhr, Fr.: 08.00 – 15.00 Uhr

1.4. Emergency telephone

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazard Statements:

Highly flammable liquid and vapour.

2.2. Label elements

Regulation (EC) No. 1272/2008

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 2 of 8

3.2. Mixtures

Hazardous components

CAS No	Chemical name					
	EC No	Index No	REACH No			
	Classification according to Regulation (EC) No. 1272/2008 [CLP]					
64-17-5	ethanol, ethyl alcohol					
	200-578-6	603-002-00-5				
	Flam. Liq. 2; H225	Flam. Liq. 2; H225				
64-19-7	Acetic acid 100 %					
	200-580-7					
	Flam. Liq. 3, Skin Corr. 1A; H226 H314					

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air.

After contact with skin

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

No direct artificial respiration to be given by first aider. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

Dizziness, Vomiting, Respiratory complaints.

Inhalation causes narcotic effects/intoxication.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 3 of 8

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges.

Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

storage temperature: at room temperature

7.3. Specific end use(s)

Use as laboratory reagent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
64-19-7	Acetic acid	10	25		TWA (8 h)	EU
		15	37	ĺ	STEL (15 min)	EU
64-17-5	Ethanol	1000	1920	ĺ	TWA (8 h)	WEL
		-	-	ĺ	STEL (15 min)	WEL

8.2. Exposure controls







Protective and hygiene measures

Take off contaminated clothing. Wash hands before breaks and after work. When using do not eat or drink.





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 4 of 8

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid

Colour: light green - yellow Odour: characteristic

Test method

pH-Value: This information is not available.

Changes in the physical state

Melting point:

Initial boiling point and boiling range:

78 °C

Flash point:

12 °C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 3,5 vol. %
Upper explosion limits: 15 vol. %
Ignition temperature: 400 °C

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: 58 hPa

(at 20 °C)

Vapour pressure: 293 hPa

(at 50 °C)

Density (at 20 °C): 0,83 g/cm³ Water solubility: easily soluble

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient: not determined





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 5 of 8

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

Rubber articles, Plastic articles

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
64-17-5	ethanol, ethyl alcohol					
	oral	LD50	6200 mg/kg	Rat	IUCLID	
	inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS	
64-19-7	Acetic acid 100 %					
	oral	LD50	3310 mg/kg	Rat	GESTIS	

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h] [d]	Species	Source		
64-17-5	ethanol, ethyl alcohol							
	Acute crustacea toxicity	EC50 mg/l	9268 - 14221	48 h	Daphnia magna	IUCLID		
64-19-7	Acetic acid 100 %							
	Acute fish toxicity	LC50	88 mg/l		Pimephales promelas (fathead minnow)	GESTIS		
	Acute crustacea toxicity	EC50	65 mg/l	48 h	Daphnia magna	Janssen et al		





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 6 of 8

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31
64-19-7	Acetic acid 100 %	-0,17

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es): 3
14.4. Packing group: II





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 7 of 8

Hazard label: 3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 144
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 80,55 % (668,565 g/l)





according to Regulation (EC) No 1907/2006

Eosin Y solution Ulm

Print date: 21.07.2016 Product code: 2C-307 Page 8 of 8

2004/42/EC (VOC): 80,55 % (668,565 g/l)

Additional information

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)