



according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Dammar - Xylene

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Waldeck GmbH & Co KG

Division Chroma

Street: Havixbecker Str. 62
Place: D-48161 Münster

Post-office box: 410180

D-48065 Münster

Telephone: +49(0)180/2247662 Telefax: +49(0)180/1247662

Responsible Department: Labor

Mo. – Do.: 08.00 – 17.00 Uhr, Fr.: 08.00 – 15.00 Uhr

1.4. Emergency telephone +49(0)180/2247662

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 3 Acute toxicity: Acute Tox. 4

Skin corrosion/irritation: Skin Irrit. 2

Hazard Statements:

Flammable liquid and vapour.

Causes skin irritation. Harmful if inhaled.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

xylene

Signal word: Warning

Pictograms:





Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation. H332 Harmful if inhaled.





according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 2 of 9

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P403+P235 Store in a well-ventilated place. Keep cool.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
1330-20-7	xylene			50 - < 55 %	
	215-535-7	601-022-00-9			
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. Rinse mouth immediately and drink plenty of water.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

Waldeck GmbH & Co KG



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 3 of 9

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO2), Foam, Extinguishing powder.

Unsuitable extinguishing media

Water.

5.2. Special hazards arising from the substance or mixture

Flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.





according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 4 of 9

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

Further information on storage conditions

storage temperature: at room temperature

7.3. Specific end use(s)

Use as laboratory reagent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol		Post shift

8.2. Exposure controls







Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.





according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 5 of 9

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Test method

pH-Value (at 20 °C): No data available

Changes in the physical state

Melting point: $-34\,^{\circ}\mathrm{C}$ Initial boiling point and boiling range: $137\,^{\circ}\mathrm{C}$ Flash point: $24\,^{\circ}\mathrm{C}$

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 1,0
Upper explosion limits: 8,0
Ignition temperature: ~ 465 °C

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: 8 hPa

(at 20 °C)

Density (at 20 °C): 0,86 g/cm³
Water solubility: insoluble

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient: not determined

Viscosity / dynamic: ~ 0,6 mPa·s

(at 20 °C)

Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

Waldeck GmbH & Co KG



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 6 of 9

10.1. Reactivity

Flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

ATEmix calculated

ATE (inhalative aerosol) 3,000 mg/l

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	
1330-20-7	xylene					
	oral	LD50	4300 mg/kg	Rat		
	dermal	LD50	1134 mg/kg	Rabbit		
	inhalative vapour	ATE	11 mg/l			
	inhalative aerosol	ATE	1,5 mg/l			

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

The product is not: Ecotoxic.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.





according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 7 of 9

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number:UN 130714.2. UN proper shipping name:XYLENES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1
Transport category: 3
Hazard No: 30
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number:UN 130714.2. UN proper shipping name:XYLENES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Classification code: F1
Limited quantity: 5 L
Excepted quantity: E1

Marine transport (IMDG)

14.1. UN number:UN 130714.2. UN proper shipping name:XYLENES

14.3. Transport hazard class(es): 3





according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 8 of 9

14.4. Packing group:
Hazard label: 3



Special Provisions: 223
Limited quantity: 5 L
Excepted quantity: E1
EmS: F-E. S-D

Air transport (ICAO)

14.1. UN number:UN 130714.2. UN proper shipping name:XYLENES

14.3. Transport hazard class(es):314.4. Packing group:IIIHazard label:3



Special Provisions:

Limited quantity Passenger:

Passenger LQ:

Excepted quantity:

A3

10 L

Y344

Excepted quantity:

E1

IATA-packing instructions - Passenger: 355
IATA-max. quantity - Passenger: 60 L
IATA-packing instructions - Cargo: 366
IATA-max. quantity - Cargo: 220 L

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Additional information

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 3 - highly water contaminating

Waldeck GmbH & Co KG



Safety Data Sheet



according to Regulation (EC) No 1907/2006

Dammar - Xylene

Print date: 15.04.2016 Product code: 3C-262 Page 9 of 9

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H226 Flammable liquid and vapour.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)