WALDECK

according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Schlesingers reagent

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Use as laboratory reagent

1.3. Details of the supplier of the safety data sheet

Company name: Waldeck GmbH & Co KG
Street: Havixbecker Str. 62
Place: D-48161 Münster

Post-office box: 410180

D-48065 Münster

Telephone: +49(0)180/2247662 Telefax: +49(0)180/1247662

Responsible Department: Labor

Mo. - Do.: 08.00 - 17.00 Uhr, Fr.: 08.00 - 15.00 Uhr

1.4. Emergency telephone +49(0)180/2247662

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2 Skin corrosion/irritation: Skin Corr. 1A

Serious eye damage/eye irritation: Eye Dam. 1

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Highly flammable liquid and vapour.

Causes severe skin burns and eye damage.

Causes serious eye damage.

Toxic to aquatic life with long lasting effects.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

acetone; propan-2-one; propanone **Signal word:**Danger

Pictograms:







Hazard statements

H225 Highly flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.



according to Regulation (EC) No 1907/2006

associating to reagand to in the including					
Schlesingers reagent					
Revision date: 20.03.2017	Product code: SCH60	Page 2 of 10			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.				
P273	Avoid release to the environment.				
P280	Wear protective gloves/protective clothing/eye protection/face protection.				
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.				
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.				
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.				
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
P310	Immediately call a POISON CENTER/doctor.				
P403+P235	Store in a well-ventilated place. Keep cool.				

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name				
	EC No	Index No	REACH No		
	Classification according to Regulation (EC) No. 1272/2008 [CLP]				
64-17-5	ethanol, ethyl alcohol			90 - < 95 %	
	200-578-6				
	Flam. Liq. 2; H225				
5970-45-6	Zinc acetate dihydrate				
	209-170-2				
	Acute Tox. 4, Aquatic Acute 1, Aquatic Chronic 1; H302 H400 H410				
67-64-1	acetone; propan-2-one; propanone			1 - < 5 %	
	200-662-2				
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066				

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

First aider: Pay attention to self-protection! Remove affected person from the danger area and lay down.

After inhalation

Provide fresh air. Medical treatment necessary.

After contact with skin

After contact with skin, wash immediately with polyethylene glycol, followed by plenty of water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Adverse human health effects and symptoms: Gastric perforation. Call a physician immediately. Do not allow a neutralisation agent to be drunk.

WALDECK

according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 3 of 10

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO2), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: Oxidising agent. Pyrophoric or self-heating substances.

WALDECK

according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 4 of 10

Further information on storage conditions

storage temperature: at room temperature

7.3. Specific end use(s)

Use as laboratory reagent

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	WEL
		1500	3620		STEL (15 min)	WEL
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

PNEC values

CAS No	CAS No Substance			
Environmental compartment Value				
64-17-5	64-17-5 ethanol, ethyl alcohol			

8.2. Exposure controls









Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

WALDECK

according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 5 of 10

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless
Odour: characteristic

Test method

pH-Value (at 20 °C):

Changes in the physical state

Melting point: 115 $^{\circ}$ C Initial boiling point and boiling range: 78 $^{\circ}$ C Flash point: 12 $^{\circ}$ C

Flammability

Solid: not applicable
Gas: not applicable
Lower explosion limits: 3,5 vol. %
Upper explosion limits: 15 vol. %

Auto-ignition temperature

Solid: not applicable
Gas: not applicable

Decomposition temperature: not determined

Oxidizing properties

Not oxidizing.

Vapour pressure: not determined

Density: not determined

Water solubility: miscible

(at 20 °C)

Solubility in other solvents

not determined

Partition coefficient: not determined Vapour density: not determined Evaporation rate: not determined

9.2. Other information

Solid content: not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Possibility of hazardous reactions. Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Exothermic reaction with: Base, Peroxide, Oxidising agent.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive



according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 6 of 10

mixtures with air.

10.5. Incompatible materials

Keep away from: Base, Oxidising agent, Peroxide.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64-17-5	ethanol, ethyl alcohol					
	oral	LD50 mg/kg	6200	Rat	IUCLID	
	inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS	
5970-45-6	Zinc acetate dihydrate					
	oral	LD50 mg/kg	794	Rat	(RTECS)	
67-64-1	acetone; propan-2-one; p	ropanone				
	oral	LD50 mg/kg	5800	Rat		
	dermal	LD50 mg/kg	20000	Rabbit	IUCLID	
	inhalative (4 h) vapour	LC50	76 mg/l	Rat		

Additional information on tests

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
64-17-5	ethanol, ethyl alcohol					
	Acute crustacea toxicity EC50 9268 - 14221 mg/l			Daphnia magna	IUCLID	
67-64-1	-1 acetone; propan-2-one; propanone					
	Acute fish toxicity LC50 5540 mg/l Acute crustacea toxicity EC50 6100 mg/l		l .	Onchorhynchus mykiss		
			48 h	Daphnia magna		
	Acute bacteria toxicity	(59-67,4 mg/l)		Activated sludge		

12.2. Persistence and degradability

The product has not been tested.



according to Regulation (EC) No 1907/2006

Schlesingers reagent	t
----------------------	---

Revision date: 20.03.2017 Product code: SCH60 Page 7 of 10

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
67-64-1	acetone; propan-2-one; propanone					
	Readily biodegradable (according to OECD criteria).	91 %	28			
	(IUCLID)					
	Biochemical oxygen demand (BOD)	1850 mg/g	5			
	(IUCLID)					
	Chemical oyxgen demand (COD)	2070 mg/g				

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L



according to Regulation (EC) No 1907/2006

	Schlesingers reagent	
Revision date: 20.03.2017	Product code: SCH60	Page 8 of 10

Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: 144
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-D

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1170

14.2. UN proper shipping name: ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)

14.3. Transport hazard class(es):314.4. Packing group:IIHazard label:3



Special Provisions: A3 A58 A180

Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2

IATA-packing instructions - Passenger:353IATA-max. quantity - Passenger:5 LIATA-packing instructions - Cargo:364IATA-max. quantity - Cargo:60 L

WALDECK

according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 9 of 10

14.6. Special precautions for user

No information available.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

2010/75/EU (VOC): 96 % 2004/42/EC (VOC): 96 %

Additional information

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers. Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile

work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or

nursing mothers.

Water contaminating class (D): 3 - highly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H319 Causes serious eye irritation.H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singulary responsible for adhering to existing laws and regulations.



according to Regulation (EC) No 1907/2006

Schlesingers reagent

Revision date: 20.03.2017 Product code: SCH60 Page 10 of 10

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)